

Zertifikat *Certificate*

Zertifikatsnummer *Certificate No.:*
PV 50647227 0001

Berichtsnummer *Report No.:*
CN24ZYJX 001

Genehmigungsinhaber *License Holder:*
Nanjing Solglass Science &
Technology Co., Ltd.
NO.28 East Tuanshan Road,
Lishui Development Zone,
Nanjing
211200 Jiangsu
P.R. China

Fertigungsstätte *Manufacturing Site:*
JIANGSU SHINEDAY SOLAR CO., LTD.
#26, ELECTRONIC INDUSTRIAL PARK WEST
SECTION, NORTH SIDE OF HANGZHOU ROAD,
SIHONG COUNTY ECONOMIC DEVELOPMENT ZONE,
SUQIAN CITY,
223999 Jiangsu
P.R. China

Prüfzeichen *Test Mark:*



IEC 61215
IEC 61730
Regular Production
Surveillance

www.tuv.com
ID 1111290917

Geprüft nach *Tested according to:*

IEC 61215-1:2021
IEC 61215-1-1:2021
IEC 61215-2:2021
IEC 61730-1:2023
IEC 61730-2:2023
EN IEC 61215-1:2021
EN IEC 61215-1-1:2021
EN IEC 61215-2:2021
EN IEC 61730-1:2018
EN IEC 61730-2:2018

Geräteidentifikation

Product Identification

Produkt: PV Module
Product:

Modell: Modelle sind auf nächste(r) Seite(n) gelistet
Type: *Type designation(s) are listed on the next page(s)*

Technische Daten: Class II acc. to IEC 61140
Technical Data: For other ratings, refer to the test report.

Gültig bis: 2029-09-12
Date of expiry:

Gültig ab: 2024-09-13
Valid from:

Ausstellungsdatum: 2024-09-13
Date of issue:

Zertifizierungsstelle:
Certification body:

Angela Yao



Dem Zertifikat liegt unsere Prüf- und Zertifizierungsordnung zugrunde.
Das Produkt entspricht den o.g. Anforderungen, die Herstellung wird überwacht.
This certificate is based on our Testing and Certification Regulation. The product fulfills above mentioned requirements, the production is subject to surveillance.

TÜV Rheinland LGA Products GmbH, Tillystraße 2, 90431 Nürnberg
<http://www.tuv.com/safety> E-mail: markcheck@tuv.com
Fax: +49 221 806-3935

Zertifikat *Certificate*

Zertifikatsnummer *Certificate No.:*

PV 50647227 0001

Berichtsnummer *Report No.:*

CN24ZYJX 001

Produkt *Product:* PV Module**Modell** *Type:***Bezeichnung** *Designation:*

Max. system voltage: up to 1000 VDC (Voc at STC):

With 1/2 cut of mono c-Si cells:

SolartrixE 1200-400-xx (xx = 47.5-65, in steps of 2.5, 18 cells)

xxx represents output power in Wp

Remarks:

Fire Rating: Class C (according to UL 790)

Design Load / Safety Factors: 3600 Pa / 1.5 (downward)

1600 Pa / 1.5 (upward)

Conditions:

The product test is voluntarily according to technical regulations. Any change of the design, materials, components or processing may require the repetition of some of the qualification tests in order to retain type approval.

